

# Pipe on Pipe Lubricant

High tech lubricant concentrate for horizontal drilling.  
Onshore & Offshore both

<b>Product Name</b>	<b>PIPE ON PIPE LUBRICANT</b>
<b>CAS No</b>	<b>72102-30-8</b>
<b>Appearance</b>	<b>Brown to Amber viscous oil</b>
<b>Chemical Formula</b>	<b>Proprietary</b>
<b>Freezing Point:</b>	<b>&lt;-10°C</b>
<b>Specific Gravity:</b>	<b>0.90</b>
<b>Boiling Point:</b>	<b>&gt;270°C</b>
<b>Solubility in H<sub>2</sub>O:</b>	<b>Dispersible</b>
<b>Vapor Pressure:</b>	<b>&lt;0.05</b>

## PACKAGING

265 US Gallon Tote | 200 Liter Barrel

## USAGE LEVEL

The efficiency of POP in low use levels. For typical 800-1000 bbl system, add 1-1/2 barrels (200 Liter each) Addition level 1 Barrel per hour. Add the POP lube slowly into the suction pit as close to the suction line as possible.

POP is an oil soluble product and will not mix readily with the drilling fluid.



Cultivating Diverse Chemistries

R-2057 Akshar Business Park  
Sector 19F, Vashi, Navi Mumbai  
T 91 22 20870030 | [info@geoconproducts.com](mailto:info@geoconproducts.com)  
[www.geoconproducts.com](http://www.geoconproducts.com)

This document is provided for informational purposes only and is based on technical information that to the best knowledge of Geocon Group on the date issued, is believed to be reliable. This document refers only to the specific material named and does not relate to its use in combination with any other material or process. This document is provided at no charge and accordingly, no warranties of any kind, express or implied, are made regarding the technical data and information provided. Furthermore, Geocon Products assumes no liability or obligation in connection with use of this information. To obtain the most accurate and current information, consult the appropriate Safety Data Sheet (SDS) prior to use of the material named herein.